

K-T AG-K ISO 7-1 2 VA

Male branch tees, conical male thread acc. to ISO 7-1, stainless steel

HANSA FLEX

Īpašības

Spiediena diapazons	Max. 25 bar
ieteicamās šļūtenes	PTFE hose
Temperatūras diapazons	-40 °C to +200 °C (depending on the hose quality and diameter)
Materiāls	Nerūsējošais tērauds 1.4404
Blīvējums	Pure metal



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

Izstrādājums

Apzīmējums	Vītnes	šļūtenei	L1 (mm)	L2 (mm)	SW1 (mm)	SW2 (mm)
K- 07 40 30 43	R 1/8	6 mm / 4 mm	46,0	17,0	12	10
K- 07 40 30 44	R 1/8	8 mm / 6 mm	46,0	17,0	14	10
K- 07 40 30 41	R 1/4	6 mm / 4 mm	46,0	21,5	12	10
K- 07 40 30 42	R 1/4	8 mm / 6 mm	46,0	21,5	14	10
K- 07 40 30 40	R 1/4	10 mm / 8 mm	52,0	21,5	16	12