K-SCHLAUCH KUPPLUNG SET STAN

Hose and coupling kits, with straight hose and DN 7.6 standard coupling

Īpašības

Ekspluatācijas spiediens	16 bar
Vielas temperatūra	-20 °C to +60 °C



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

Izstrādājums

Apzīmējums	Šļūtenes izmērs	Darba garums (m)
K- 07 10 05 62	12 mm x 8 mm	10,0
K- 07 10 05 63	12 mm x 8 mm	15,0
K- 07 10 05 64	16 mm x 11 mm	10,0
K- 07 10 05 65	16 mm x 11 mm	15,0

Neskatoties uz rūpīgu pārbaudi, mēs nevaram izslēgt kļūdas un negarantējam iekļautās informācijas pareizību.