

K-SCHLAUCH KUPPLUNG SET STAN

Hose and coupling kits, with straight hose and DN 7.6 standard coupling

HANSA FLEX

Īpašības

| | |
|--------------------------|------------------|
| Ekspluatācijas spiediens | 16 bar |
| Vielas temperatūra | -20 °C to +60 °C |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

Izstrādājums

| Apzīmējums | Šļūtenes izmērs | Darba garums (m) |
|----------------|-----------------|---------------------|
| K- 07 10 05 62 | 12 mm x 8 mm | 10,0 |
| K- 07 10 05 63 | 12 mm x 8 mm | 15,0 |
| K- 07 10 05 64 | 16 mm x 11 mm | 10,0 |
| K- 07 10 05 65 | 16 mm x 11 mm | 15,0 |