
K-WV 3/2 LB NAMUR GETAUSCHT

3/2-way spool valves with NAMUR style interface, NC, ports 1 and 3 or 2 and 3 swapped

HANSA-FLEX

Īpašības

Darba vides	Air, neutral gases, filtered
Darba spiediens	1.5 to 10 bar
Ekspluatācijas temperatūra	-20 °C to +70 °C
Elektriskais pieslēgums	Plug connector PG 9
Iekļauts piegādes komplektācijā	Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws
Jaudas patēriņš	3 W=/5 VA~
Korpuss	Aluminium, anodised
Aizbīdnis	Stainless steel
Blīvēšanas materiāls	NBR



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.
Two or three-piece service units with excellent flow rates in modern design.
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Izstrādājums

Apzīmējums	Spriegums	Savienojums	DN	Caurplūde (L/min)
K- 07 15 00 05	230 V, 50 Hz	G 1/4	7	1250
K- 07 15 00 06	24 V DC	G 1/4	7	1250