

# K-DROSSELPLATT NAMUR VENTIL

Flow regulators for NAMUR valves

**HANSA FLEX**

## Īpašības

|                                 |   |
|---------------------------------|---|
| Darba vides                     | Air, neutral gases, filtered                                  |
| Darba spiediens                 | 0.5 to 10 bar   |
| Ekspluatācijas temperatūra      | -20 °C to +70 °C  |
| Iekļauts piegādes komplektācijā | 1 coding pin (not for K-07152240), 2 O-rings, 2 fixing screws |
| Korpuss                         | Aluminium, anodised   |
| Materiāls                       | Blīvējums: NBR  |
| Blīvēšanas materiāls            | NBR   |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard. 3/2-way flow regulators: Independent regulation of the forward and return strokes of a single-acting pneumatic actuator. 5/2-way flow regulators: Regulation of the forward and return strokes of a double-acting pneumatic actuator.

## Izstrādājums

| Apzīmējums     | Funkcija | Darbība       | DN | Caurplūde (L/min) |
|----------------|----------|---------------|----|-------------------|
| K- 07 15 22 39 | 3/2-way  | Knurled Screw | 5  | 650               |
| K- 07 15 22 40 | 3/2-way  | Screwdriver   | 5  | 650               |
| K- 07 15 22 41 | 5/2-way  | Knurled Screw | 5  | 650               |
| K- 07 15 22 42 | 5/2-way  | Screwdriver   | 5  | 650               |