

K-ZWEIHAND S VENTILE O GEH

Two-hand safety valve without housing

HANSA FLEX

Īpašības

| | |
|-----------------------------------|---------------------------------------|
| Darba vides | Filtered, unlubricated compressed air |
| Ekspluatācijas spiediens | 2.5 - 8 bar |
| Temperatūras diapazons | -10 °C to +60 °C |
| Savienojums | Push-in fitting for pipe 4 mm |
| Darbība | Pneumatic |
| Gaisa caurplūdes daudzums 6 bar | 85 NI/min |
| maks. ieejas signāla laika nobīde | 0,4 s |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter. Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

Izstrādājums

| Apzīmējums | Definīcija | Savienojums |
|----------------|---------------------------------------|-------------------------------|
| K- 07 15 26 09 | Two-hand safety valve without housing | Push-in fitting for 4 mm pipe |
| K- 07 15 26 10 | mounting element | - |