K-MANO STAND H

Pressure gauges, CrNi steel, standard type, connection on rear, centrical

Īpašības

Tips	131.11
Modelis	Bourdon-tube pressure gauge, CrNi steel type
Izmantošana	For gaseous, liquid, corrosive and not crystallising media which do not have high viscosity, also in corrosive atmosphere Clean Dry Air applications, machine and plant construction
Kvalitātes klase	2,5
Vielas temperatūra	max. +100 °C
Vides temperatūra	-40 °C to +60 °C
Korpuss	CrNi steel
Skatstikls	Polycarbonate



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Standard model manufactured entirely from CrNi steel, economical and reliable.

Izstrādājums

Apzīmējums	Mērīšanas diapazons	Ø (mm)	Savienojums
K- 07 20 03 93	0 - 1.0 bar	40,0	G 1/4
K- 07 20 03 94	0 - 1.6 bar	40,0	G 1/4
K- 07 20 03 95	0 - 2.5 bar	40,0	G 1/4
K- 07 20 03 96	0 - 4.0 bar	40,0	G 1/4
K- 07 20 03 97	0 - 6.0 bar	40,0	G 1/4
K- 07 20 03 98	0 - 10.0 bar	40,0	G 1/4
K- 07 20 03 99	0 - 16.0 bar	40,0	G 1/4
K- 07 20 04 00	0 - 25.0 bar	40,0	G 1/4
K- 07 20 04 01	0 - 40.0 bar	40,0	G 1/4
K- 07 20 04 02	0 - 60.0 bar	40,0	G 1/4
K- 07 20 04 03	0 - 100.0 bar	40,0	G 1/4
K- 07 20 04 94	0 - 1.0 bar	50,0	G 1/4
K- 07 20 04 95	0 - 1.6 bar	50,0	G 1/4
K- 07 20 04 96	0 - 2.5 bar	50,0	G 1/4
K- 07 20 04 97	0 - 4.0 bar	50,0	G 1/4
K- 07 20 04 98	0 - 6.0 bar	50,0	G 1/4
K- 07 20 04 99	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 00	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 01	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 02	0 - 40.0 bar	50,0	G 1/4
K- 07 20 05 03	0 - 60.0 bar	50,0	G 1/4
K- 07 20 05 04	0 - 100.0 bar	50,0	G 1/4

Neskatoties uz rūpīgu pārbaudi, mēs nevaram izslēgt kļūdas un negarantējam iekļautās informācijas pareizību.