

K-SVKM NW 7,6 SCHL TUE ST VZ

Quick disconnect couplings DN 7.6, galvanised steel / brass, with hose connector

HANSA FLEX

Īpašības

| | |
|--------------------------|---|
| Ekspluatācijas spiediens | Max. 16 bar |
| Gaisa caurplūde | 2.100 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Vielas temperatūra | -20 °C to +100 °C |
| Korpuss | Steel |
| Atspere | Stainless-steel |
| Bīdāma uzmava | Hardened and nickel-plated steel |
| Bīvēšanas materiāls | NBR |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The "stream line" type has an integrated hose stem.

Izstrādājums

| Apzīmējums | Savienojums | Garums (mm) |
|----------------|---------------|-------------|
| K- 07 35 07 83 | Stem, I.D. 6 | 67,0 |
| K- 07 35 07 84 | Stem, I.D. 8 | 70,0 |
| K- 07 35 12 87 | Stem, I.D. 9 | 70,0 |
| K- 07 35 07 85 | Stem, I.D. 10 | 70,0 |
| K- 07 35 07 86 | Stem, I.D. 13 | 68,0 |

Papildelementi

| | |
|-------------------------------|---|
| K-NIPPEL KUPPL NW7 AG VZ PTFE | Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal |
| K-NIPPEL KUPPL NW7 IG VZ 1 | Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female |
| K-NIPPEL KUPPL STREAM LINE | Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line« |
| K-TUE 7,2 7,8 ST VZ 2 | Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel |