

# K-SVKM NW 7,8 SCHL TUE H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem

**HANSA FLEX**

## Īpašības

<b>Ekspluatācijas spiediens</b>	0 - 35 bar
<b>Gaisa caurplūde</b>	2.100 l/min (at $\Delta p = 0.5$ bar)
<b>Vielas temperatūra</b>	-20 °C to +40 °C
<b>Vītņots elements</b>	Nickel-plated brass
<b>Vārsta korpus</b>	Steel, QPQ treated
<b>Atbloķēšanas uzdeva</b>	Extremely robust, ergonomic plastic
<b>Vārsts, līgza</b>	Brass
<b>Darba vides</b>	Only for clean compressed air
<b>Bīvējumi</b>	NBR
<b>Atspere, sprostgredzens, lodes</b>	stain less steel



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

## Izstrādājums

Apzīmējums	Savienojums	Garums (mm)	SW (mm)
K- 07 35 08 53	Stem, I.D. 6	80,0	19
K- 07 35 12 41	Stem, I.D. 8	80,0	19
K- 07 35 08 54	Stem, I.D. 9	80,0	19
K- 07 35 12 42	Stem, I.D. 10	80,0	19
K- 07 35 08 55	Stem, I.D. 13	80,0	19

## Papild elementi

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass