

K-SVKM NW 7,8 SCHL TUE H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, with hose stem

HANSA FLEX

Īpašības

Ekspluatācijas spiediens	0 - 35 bar
Gaisa caurplūde	2.100 l/min (at $\Delta p = 0.5$ bar)
Vielas temperatūra	-20 °C to +40 °C
Vītņots elements	Nickel-plated brass
Vārsta korpus	Steel, QPQ treated
Atbloķēšanas uzdevs	Extremely robust, ergonomic plastic
Vārsts, līgza	Brass
Darba vides	Only for clean compressed air
Bīvējumi	NBR
Atspere, sprostgredzens, lodes	stain less steel



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Izstrādājums

Apzīmējums	Savienojums	Garums (mm)	SW (mm)
K- 07 35 08 53	Stem, I.D. 6	80,0	19
K- 07 35 12 41	Stem, I.D. 8	80,0	19
K- 07 35 08 54	Stem, I.D. 9	80,0	19
K- 07 35 12 42	Stem, I.D. 10	80,0	19
K- 07 35 08 55	Stem, I.D. 13	80,0	19

Papildielementi

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass