


K-SVKM NW 7,2 SCHL-TUE MS BL CL

Quick disconnect couplings DN 7.2, brass with a bare metal surface, with hose stem

HANSA FLEX

Īpašības

Ekspluatācijas spiediens	0 - 35 bar, maximum static working pressure (non-pulsating)
Vielas temperatūra	-20 °C to +100 °C
Korpuss, uzdeva, vārsta korpuss	Brass
Bīvēšanas materiāls	NBR
Atspere, sprostgredzens, tapas	Stainless steel



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Universal, one-hand quick disconnect couplings, one side sealing, at an unbeatably low price. Compatible with CEJN 320, Rectus 25/26 and JWL 520/530. The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

Izstrādājums

Apzīmējums	Savienojums	Garums (mm)
K- 07 35 07 45	Stem, I.D. 6	54,0
K- 07 35 07 46	Stem, I.D. 9	54,0
K- 07 35 07 47	Stem, I.D. 13	53,5
K- 07 35 07 48	Stem, I.D. 8	54,0
K- 07 35 07 49	Stem, I.D. 10	54,0