

# K-SENSOREN T-NUT 1

Sensor for T-slot

**HANSA FLEX**



## Papildu informācija

Important: The scope of supply does not include a connector. Please order separately.

Adjustable limit switches with shock absorber available on request.

## Izstrādājums

| Apzīmējums     | Modelis                                      |
|----------------|--|
| K- 07 15 20 89 | Reed sensor, 2-wire, with 2.5 m cable length |
| K- 07 15 20 90 | Reed sensor, 2-wire, with M 8 plug (3-pin)   |
| K- 07 15 20 93 | Hall sensor, 3-wire, with M 8 plug (3-pin)   |

## ir piederums šādiem izstrādājumiem

|                           |  |
|---------------------------|--|
| K-RUNDZYLINDER DOPP O E D | Round cylinders, double acting, magnetic, non-cushioned      |
| K-RUNDZYLINDER DOPP O D   | Miniature cylinders, double acting (magnetic, non-cushioned) |
| K-RUNDZYLINDER EINF O D   | Miniature cylinders, single-acting (magnetic, non-cushioned) |
| K-RUNDZYLINDER DOPP O D 1 | Round cylinders, double acting (magnetic, non-cushioned)     |
| K-NORMZYLINDER            | Standard cylinders   |
| K-KOLST LOSE ZYL          | Rodless cylinders  |