

K-ENDPLATTEN V

End plate for HDM valve terminal

Īpašības

| | |
|-------------------------------|---|
| Darba vides | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| Darba spiediens | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard) |
| Regulēšanas spiediens | 3 - 7 bar |
| Temperatūras diapazons | -10 °C to +60 °C |
| Caurplūde | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8) |
| Vadību skaits | Max. 16 (e.g. 16 spring return valves) |
| Funkcija | Blind (terminates the system) |
| Manuāla palīgvadība | Latching (bistable), Monostable (non-latching) version also available on request |
| Jaudas patēriņš | 0.6 W per pilot |
| Aizsardzības veids | IP 65 |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Papildu informācija

Important: The scope of supply does not include a connector. Please order separately.

Izstrādājums

| Apzīmējums | Funkcija |
|----------------|-------------------------------|
| K- 07 15 22 50 | Blind (terminates the system) |