


# K-ADA HUTPROFIL

Adapter for DIN rail

**HANSA FLEX**

## Īpašības

<b>Darba vides</b>	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
<b>Darba spiediens</b>	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
<b>Regulēšanas spiediens</b>	3 - 7 bar
<b>Temperatūras diapazons</b>	-10 °C to +60 °C
<b>Caurplūde</b>	200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8)
<b>Vadību skaits</b>	Max. 16 (e.g. 16 spring return valves)
<b>Manuāla palīgvadība</b>	Latching (bistable), Monostable (non-latching) version also available on request
<b>Jaudas patēriņš</b>	0.6 W per pilot
<b>Aizsardzības veids</b>	IP 65



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Papildu informācija

Important: The scope of supply does not include a connector. Please order separately.

## Izstrādājums

Apzīmējums	Definīcija
K- 07 15 22 43	Adapter for DIN rail