


K-WTEH SERIE ONE O DRS

Service units, »ONE« Series, without pressure switch

HANSA FLEX

Īpašības

ļeejas spiediens	Max. 10 bar
Temperatūras diapazons	-10 °C to +50 °C
Darba vides	Saspiests gaiss
Aizsardzības veids	IP 65
Darba spiediens	0.5 - 8 bar
Spiediena slēdzis	Changeover contact
Poru attālums filtra elementā	20 µm
Caurplūdes vērtības mērījums	At 6,3 bar and Δp = 1 bar



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Multifunctional service unit with 6 or 7 functions in a single device: 3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional: pressure switch. This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market! Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

Pasūtījuma norādes

This unit can also be supplied with many other combinations of functions and port sizes. We will be pleased to make you an offer to match your individual specification on request!

Izstrādājums

Apzīmējums	Savienojums	Caurplūde (L/min)	A (mm)	B	C (mm)	Spriegums
K- 07 25 13 79	G 1/4	2400	165,5	144,0 mm	35,0	24 V DC (for valves and pressure switch)
K- 07 25 13 80	G 3/8	3300	165,5	144,0 mm	35,0	24 V DC (for valves and pressure switch)
K- 07 25 13 81	G 1/2"	4000	165,5	144,0 mm	35,0	24 V DC (for valves and pressure switch)