


K-WV 3/2 5/2 NAMUR LB FR

3/2- and 5/2-way spool valves with NAMUR style interface and combined spring return

HANSA FLEX

Īpašības

| | |
|---------------------------------|--|
| Darba vides | Air, neutral gases (filtered) |
| Darba spiediens | 1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22) |
| Eksploatācijas temperatūra | -20 °C to +50 °C |
| Savienojums 1 - 3 | G 1/4 (Port 1), G 1/4 (Port 3 and 5) |
| Pieslēgums 1/3 + 5 | G 1/4 (Port 1), G 1/4 (Port 3 and 5) |
| Elektriskais pieslēgums | Plug connector PG 9 |
| Iekļauts piegādes komplektācijā | Plug connector PG 9, conversion plate, screws and seal |
| Jaudas patēriņš | 3 W=5 VA~ |
| Korpuss | Anodised aluminium |
| Aizbīdnis | Stainless steel |
| Bīvēšanas materiāls | NBR |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

Izstrādājums

| Apzīmējums | Spriegums | Port 1 | Pieslēgums 3 + 5 | DN | Caurplūde (L/min) |
|----------------|--------------|--------|------------------|----|-------------------|
| K- 07 15 00 15 | 230 V, 50 Hz | G 1/4 | G 1/4 | 7 | 1250 |
| K- 07 15 00 16 | 24 V DC | G 1/4 | G 1/4 | 7 | 1250 |