

K-WV 3/2 5/2 NAMUR LB FR

3/2- and 5/2-way spool valves with NAMUR style interface and combined spring return

HANSA FLEX

Īpašības

Darba vides	Air, neutral gases (filtered)
Darba spiediens	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
Eksploatācijas temperatūra	-20 °C to +50 °C
Savienojums 1 - 3	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Pieslēgums 1/3 + 5	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Elektriskais pieslēgums	Plug connector PG 9
Iekļauts piegādes komplektācijā	Plug connector PG 9, conversion plate, screws and seal
Jaudas patēriņš	3 W=5 VA~
Korpuss	Anodised aluminium
Aizbīdnis	Stainless steel
Bīvēšanas materiāls	NBR



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

Izstrādājums

Apzīmējums	Spriegums	Port 1	Pieslēgums 3 + 5	DN	Caurplūde (L/min)
K- 07 15 00 15	230 V, 50 Hz	G 1/4	G 1/4	7	1250
K- 07 15 00 16	24 V DC	G 1/4	G 1/4	7	1250