


# K-VSTO POM

## Plugs

### Īpašības

Darba spiediens	0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)
Eksploataācijas temperatūra	-20 °C to +70 °C in air; +1 °C to +70 °C in water
Materiāls	Acetalpolymerisat (POM)
Blīvēšanas materiāls	NBR



### Norāde

Citi dati pieejami pēc pieprasījuma.

### Apraksts

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

### Izstrādājums

Apzīmējums	Krāsa	L1 (mm)	Īscaurule (mm)
K- 07 40 29 11	sarkans	28,0	4
K- 07 40 29 12	sarkans	28,0	5
K- 07 40 29 13	sarkans	30,0	6
K- 07 40 29 14	sarkans	31,0	8
K- 07 40 29 15	sarkans	36,5	10
K- 07 40 29 16	sarkans	38,5	12
K- 07 40 29 17	melns	45,0	15
K- 07 40 29 18	melns	41,5	18
K- 07 40 29 19	melns	45,0	22
K- 07 40 29 20	melns	56,0	28