

# K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type

**HANSA FLEX**

## Īpašības

<b>Ekspluatācijas spiediens</b>	maks. 10 bar
<b>Gaisa caurplūde</b>	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
<b>Vielas temperatūra</b>	-20 °C to +150 °C
<b>Korpuss</b>	Stainless steel 1.4404
<b>Vītne</b>	Stainless steel 1.4404
<b>Iekšējās daļas</b>	Stainless steel 1.4404
<b>Poga, vārsts</b>	Stainless steel 1.4404
<b>Bīvēšanas materiāls</b>	FKM



## Norāde

Not suitable for hitting / pulsating tools.

Citi dati pieejami pēc pieprasījuma.

## Apraksts

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

## Papildu informācija

Not suitable for hitting / pulsating tools.

## Izstrādājums

Apzīmējums	Savienojums	Garums (mm)	SW (mm)
<b>K- 07 35 12 79</b>	G 1/4 female	71,5	21
<b>K- 07 35 12 80</b>	G 3/8 female	75,5	21
<b>K- 07 35 12 81</b>	G 1/2 female	77,5	24