


K-LKM S NW7,4 DREH AG VA

Safety couplings DN 7.4, stainless steel 1.4404, male, swivel type

HANSA FLEX

Īpašības

Ekspluatācijas spiediens	maks. 10 bar
Gaisa caurplūde	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Vielas temperatūra	-20 °C to +150 °C
Korpuss	Stainless steel 1.4404
Vītne	Stainless steel 1.4404
Iekšējās daļas	Stainless steel 1.4404
Poga, vārsts	Stainless steel 1.4404
Bīvēšanas materiāls	FKM



Norāde

Not suitable for hitting / pulsating tools.

Citi dati pieejami pēc pieprasījuma.

Apraksts

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Papildu informācija

Not suitable for hitting / pulsating tools.

Izstrādājums

Apzīmējums	Savienojums	Garums (mm)	SW (mm)
K- 07 35 12 76	G 1/4 male	70,5	21
K- 07 35 12 77	G 3/8 male	70,0	21
K- 07 35 12 78	G 1/2 male	72,5	25