


# K-DV GEW B SCHLITZ

Bidirectional flow control valves, air restriction at both ends (»B«), screw connection

**HANSA FLEX**

## Īpašības

<b>Ekspluatācijas spiediens</b>	maks. 10 bar
<b>Temperatūras diapazons</b>	0 °C to +70 °C
<b>Dobskrūve, pagriežama svira, regulēšanas skrūve</b>	Nickel-plated brass
<b>Iekšējās daļas</b>	Brass with a bare metal surface
<b>Blīvgredzena apmales blīvējums</b>	NBR
<b>Blīvējumi (nepazaudējami)</b>	Polyamide (glass fibre-reinforced)



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. Compact type of construction, also ideal where space is restricted.

## Izstrādājums

Apzīmējums	Savienojums	C (mm)	Vītnes	SW	B (mm)
K- 07 15 05 53	M 5 female thread	11,5	M 5	8 mm	24,5
K- 07 15 05 58	G 1/8 female thread	16,0	G 1/8	14 mm	32,0
K- 07 15 05 54	G 1/4 female thread	22,0	G 1/4	17 mm	40,0
K- 07 15 25 26	G 3/8 female thread	26,0	G 3/8	20 mm	50,0
K- 07 15 25 25	G 1/2 female thread	32,0	G 1/2	26 mm	61,0