


# K-STECKVERBINDU 1

Straight push-in connector

**HANSA FLEX**

## Īpašības

|                            |                  |
|----------------------------|------------------|
| Darba spiediens            | Max. 16 bar      |
| Ekspluatācijas temperatūra | -20 °C to +80 °C |
| Materiāls                  | Niķelēts misiņš  |
| Piespiedējgredzens         | Hostaform        |
| Iespīlēšanas gredzens      | Stainless steel  |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Izstrādājums

| Apzīmējums     | Vītnes     | šļūtenes ārējam Ø | L1<br>(mm) |
|----------------|------------|-------------------|------------|
| K- 07 40 25 18 | M 8 x 0.75 | 3 mm              | 18,4       |
| K- 07 40 25 19 | M 11 x 1   | 4 mm              | 30,6       |
| K- 07 40 25 20 | M 14 x 1   | 5 mm              | 33,5       |
| K- 07 40 25 21 | M 13 x 1   | 6 mm              | 33,0       |
| K- 07 40 25 22 | M 15 x 1   | 8 mm              | 35,7       |
| K- 07 40 25 23 | M 17 x 1   | 10 mm             | 39,2       |
| K- 07 40 25 24 | M 20 x 1   | 12 mm             | 39,7       |
| K- 07 40 25 25 | M 24 x 1   | 14 mm             | 45,9       |