K-DMUF FESTSTOFFHALTIGE MED

Pressure transmitter for viscous and solids-containing media, nonlinearity 0.2%

Īpašības

Tips	S-11
Spriegums	DC 10 (14) ... 30 V
Elektriskais pieslēgums	With right-angle connector acc. to DIN EN 175301-803 A
Aizsardzības veids	IP 65 acc. to EN 60529
Izejas signāls	4 to 20 mA, 2-wire
Nelinearitāte	0.2% of span
Vielas temperatūra	-30 °C to +100 °C; (Range: 400 and 600 bar: -30 °C to +70 °C)
Vides temperatūra	-20 °C to +80 °C
Daļas, kas saskaras ar mērīšanas vielu	CrNi steel 1.4571
Korpuss	CrNi steel 1.4571



Apraksts

Pressure transmitter in CrNi steel with flush diaphragm for measuring viscous, pasty, adhesive, crystallising, particle-laden or contaminated media, which would clog the pressure channel of conventional process connections. Applications: Electronic pressure measurement in the food and beverages sector, hydraulic power units or industrial applications in general.

Papildu informācija

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Izstrādājums

Apzīmējums	Mērīšanas diapazons	Vītnes
K- 07 20 12 38	0 - 0.25 bar	G 1
K- 07 20 12 39	0 - 0.4 bar	G 1
K- 07 20 12 40	0 - 1.0 bar	G 1
K- 07 20 12 41	0 - 10.0 bar	G 1/2
K- 07 20 12 42	0 - 100.0 bar	G 1/2
K- 07 20 12 43	0 - 16.0 bar	G 1/2
K- 07 20 12 44	0 - 160.0 bar	G 1/2
K- 07 20 12 45	0 - 25.0 bar	G 1/2
K- 07 20 12 46	0 - 250.0 bar	G 1/2
K- 07 20 12 47	0 - 4.0 bar	G 1/2
K- 07 20 12 48	0 - 40.0 bar	G 1/2
K- 07 20 12 49	0 - 400.0 bar	G 1/2
K- 07 20 12 50	0 - 6.0 bar	G 1/2
K- 07 20 12 51	0 - 60.0 bar	G 1/2
K- 07 20 12 52	0 - 600.0 bar	G 1/2

Rezerves daļas

K-ZUBEH DRUCKMESSUMFOR	Accessoires for pressure transmitters for viscous and solids-containing media, nonlinearity 0.2%

Neskatoties uz rūpīgu pārbaudi, mēs nevaram izslēgt kļūdas un negarantējam iekļautās informācijas pareizību.