



K-STECKVERSCHR AGR OR SK

Male connectors, parallel male thread with O-ring and outer hex

HANSA FLEX

Īpašības

| | |
|------------------------|--|
| Darba spiediens | Max. 15 bar, coarse vacuum |
| Izmantošana | Air, vacuum |
| Ieteicamās šļūtenes | PU or PA (nylon) |
| Darba vides | Compressed air and all gases or liquids that are compatible with the materials |
| Temperatūras diapazons | -20 °C to +80 °C |
| Bīvēšanas virsma | Parallel version: O-ring in housing |
| Materiāls | Plastic, Nickel plated brass |
| Piespiedējgredzens | Plastic |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Izstrādājums

| Apzīmējums | Vītne | šļūtenes ārējais Ø | Sešstūra iedobe (mm) | L1 (mm) | SW |
|----------------|-------|--------------------|----------------------|---------|-------|
| K- 07 40 00 78 | M 5 | 4 mm | 2,0 | 20,8 | 10 mm |
| K- 07 40 00 79 | M 5 | 6 mm | 2,0 | 22,2 | 12 mm |
| K- 07 40 00 92 | G 1/8 | 4 mm | 3,0 | 19,3 | 10 mm |
| K- 07 40 00 93 | G 1/8 | 6 mm | 4,0 | 20,2 | 12 mm |
| K- 07 40 00 94 | G 1/8 | 8 mm | 5,0 | 27,1 | 14 mm |
| K- 07 40 00 90 | G 1/8 | 10 mm | 5,0 | 28,9 | 17 mm |
| K- 07 40 00 91 | G 1/8 | 12 mm | 5,0 | 31,6 | 21 mm |
| K- 07 40 00 87 | G 1/4 | 4 mm | 3,0 | 17,4 | 10 mm |
| K- 07 40 00 88 | G 1/4 | 6 mm | 4,0 | 20,9 | 12 mm |
| K- 07 40 00 89 | G 1/4 | 8 mm | 6,0 | 23,0 | 14 mm |
| K- 07 40 00 85 | G 1/4 | 10 mm | 6,0 | 29,9 | 17 mm |
| K- 07 40 00 86 | G 1/4 | 12 mm | 6,0 | 32,6 | 21 mm |
| K- 07 40 00 98 | G 3/8 | 6 mm | 4,0 | 19,5 | 12 mm |
| K- 07 40 00 99 | G 3/8 | 8 mm | 6,0 | 22,1 | 14 mm |
| K- 07 40 00 95 | G 3/8 | 10 mm | 8,0 | 25,9 | 17 mm |
| K- 07 40 00 96 | G 3/8 | 12 mm | 8,0 | 28,6 | 21 mm |
| K- 07 40 00 97 | G 3/8 | 16 mm | 8,0 | 36,1 | 24 mm |
| K- 07 40 00 83 | G 1/2 | 6 mm | 4,0 | 22,6 | 12 mm |
| K- 07 40 00 84 | G 1/2 | 8 mm | 6,0 | 23,2 | 14 mm |
| K- 07 40 00 80 | G 1/2 | 10 mm | 8,0 | 24,5 | 17 mm |
| K- 07 40 00 81 | G 1/2 | 12 mm | 8,0 | 31,1 | 21 mm |
| K- 07 40 00 82 | G 1/2 | 16 mm | 10,0 | 38,1 | 24 mm |