

# K-STECKVERBINDU 10BAR

Straight push-in connector (pressure max. 10 bar)

**HANSA FLEX**

## Īpašības

|                               |  |
|-------------------------------|--|
| <b>Darba spiediens</b>        | Max. 10 bar  |
| <b>Izmantošana</b>            | Air, vacuum  |
| <b>Ieteicamās šļūtenes</b>    | PU or PA (nylon)   |
| <b>Darba vides</b>            | Compressed air and all gases or liquids that are compatible with the materials |
| <b>Temperatūras diapazons</b> | -20 °C to +80 °C   |
| <b>Materiāls</b>              | Plastic, Nickel plated brass   |
| <b>Piespiedējgredzens</b>     | Plastic  |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Izstrādājums

| Apzīmējums     | šļūtenes ārējais Ø | L1<br>(mm) |
|----------------|--------------------|------------|
| K- 07 40 03 39 | 4 mm               | 33,0       |
| K- 07 40 03 40 | 6 mm               | 34,6       |
| K- 07 40 03 41 | 8 mm               | 38,5       |
| K- 07 40 03 42 | 10 mm              | 47,0       |
| K- 07 40 03 43 | 12 mm              | 48,6       |
| K- 07 40 41 32 | 14 mm              | 48,7       |
| K- 07 40 03 44 | 16 mm              | 49,8       |