

# K-STECKVERBINDU 2

Straight push-in connector

**HANSA FLEX**

## Īpašības

|                            |                     |
|----------------------------|---------------------|
| Darba spiediens            | Max. 16 bar         |
| Ekspluatācijas temperatūra | -20 °C to +150 °C   |
| Materiāls                  | Niķelēts misiņš     |
| Piespiedējgredzens         | Nickel-plated brass |
| Iespīlēšanas gredzens      | Stainless steel     |



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

## Izstrādājums

| Apzīmējums     | šļūtenes ārējam Ø | L1<br>(mm) |
|----------------|-------------------|------------|
| K- 07 40 27 49 | 4 mm              | 31,0       |
| K- 07 40 27 50 | 6 mm              | 33,0       |
| K- 07 40 27 51 | 8 mm              | 37,0       |
| K- 07 40 27 52 | 10 mm             | 39,0       |
| K- 07 40 47 74 | 12 mm             | 43,0       |
| K- 07 40 40 91 | 14 mm             | 47,5       |