

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Īpašības

Iekšējā kārtā	Soft-PVC, black
Ieliktnis	poliestera appinums
Ārskats	Soft-PVC, blue
Temperatūra	-20 °C to +60 °C
Rullja garums	50 m



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Izstrādājums

Apzīmējums	Ø šļūtenei iekšpusē (mm)	Ø šļūtenei ārpusē (mm)	Max. working pressure resistance at 23°C (bar)	Min. liekuma rādiuss (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88