

K-LKM S NW7,2 SCHL TUE

Safety couplings DN 7.2, with hose stem

HANSA FLEX

Īpašības

Ekspluatācijas spiediens	0 - 35 bar, maximum static working pressure (non-pulsating)
Gaisa caurplūde	1.100 l/min (at $\Delta p = 0.5$ bar)
Vielas temperatūra	-30 °C to +100 °C
Korpuss, uzmava, vārsta korpuss	Nickel-plated brass
Atspere, lodes	Stainless-steel
Blīvēšanas materiāls	NBR



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

One-hand safety coupling with double locking mechanism. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then be relieved from the plug side (hose). The second locking mechanism is released by actuating the unlocking sleeve again. The coupling can now be disconnected.

Izstrādājums

Apzīmējums	Savienojums	Garums (mm)	SW (mm)
K- 07 35 02 87	Stem, I.D. 6	60,0	22
K- 07 35 02 88	Stem, I.D. 8	60,0	22
K- 07 35 02 89	Stem, I.D. 9	60,0	22
K- 07 35 02 90	Stem, I.D. 10	60,0	22
K- 07 35 02 91	Stem, I.D. 13	60,0	22

Papildēlementi

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,