


# K-STECKNIPPEL 1

push-in plugs

**HANSA FLEX**

## Īpašības

<b>Darba spiediens</b>	Max. 15 bar, coarse vacuum
<b>Izmantošana</b>	Air, vacuum
<b>ieteicamās šļūtenes</b>	PU or PA (nylon)
<b>Darba vides</b>	Compressed air and all gases or liquids that are compatible with the materials
<b>Temperatūras diapazons</b>	-20 °C to +80 °C
<b>Bļivēšanas virsma</b>	Parallel version: O-ring in housing, Conical version: thread coating
<b>Materiāls</b>	Plastic, Nickel plated brass
<b>Piespiedējgredzens</b>	Plastic



## Norāde

Citi dati pieejami pēc pieprasījuma.

## Apraksts

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Izstrādājums

Apzīmējums	šļūtenes ārējais Ø	L1 (mm)
K- 07 40 42 78	4 mm	36,0
K- 07 40 42 79	6 mm	38,0
K- 07 40 42 80	8 mm	38,0
K- 07 40 42 81	10 mm	40,2
K- 07 40 42 82	12 mm	44,0