K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

Īpašības

Izmantošana	Air, gases, oils, greases, fuels, organic and inorganic substances
Ekspluatācijas temperatūra	-40 °C to +100 °C
Pieslēguma veids	connection nipples and coupling NW 7,2



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Izstrādājums

Apzīmējums	Ø šļūtenei iekšpusē (mm)	Ø šļūtenei ārpusē (mm)	Ø spirālei ārpusē (mm)	Tinumi	Max. working pressure resistance at 23° C (bar)	maks. darba garums (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

Piederumi

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector

Neskatoties uz rūpīgu pārbaudi, mēs nevaram izslēgt kļūdas un negarantējam iekļautās informācijas pareizību.