

K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug,
bare brass

HANSA FLEX

Ipašības

Pieslēguma veids	connection nipples and coupling NW 7,2
Ekspluatācijas temperatūra	-40 °C to +74 °C



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Izstrādājums

Apzīmējums	Ø šķūtenei iekšpusē (mm)	Ø šķūtenei ārpusē (mm)	Ø ārējam tinumam (mm)	Max. working pressure resistance at 23°C (bar)	maks. darba garums (m)
K-07 10 12 72	5,0	8,0	40	10	3,0
K-07 10 12 74	5,0	8,0	40	10	6,0
K-07 10 12 76	5,0	8,0	40	10	7,5
K-07 10 12 81	6,3	9,5	60	10	3,0
K-07 10 12 83	6,3	9,5	60	10	6,0
K-07 10 12 85	6,3	9,5	60	10	7,5
K-07 10 12 79	6,3	9,5	60	10	10,0
K-07 10 12 90	8,0	12,0	80	9	3,0
K-07 10 12 92	8,0	12,0	80	9	6,0
K-07 10 12 94	8,0	12,0	80	9	7,5
K-07 10 12 88	8,0	12,0	80	9	10,0

Piederumi

K-DREHBARE VERSCHRAUBUNG	Swivel adapters
--------------------------	-----------------