

K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

HANSA FLEX

Īpašības

| | |
|----------------------------|--|
| Pieslēguma veids | with pushbutton safety coupling NW 7,4 steel nipple galvanised |
| Ekspluatācijas temperatūra | -40 °C to +74 °C |



Norāde

Citi dati pieejami pēc pieprasījuma.

Apraksts

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Nav piemērota darbarīkiem, kas rada triecienus vai pulsāciju!

Izstrādājums

| Apzīmējums | Ø šļūtenei iekšpusē (mm) | Ø šļūtenei ārpusē (mm) | Ø ārējam tinumam (mm) | Max. working pressure resistance at 23°C (bar) | maks. darba garums (m) |
|----------------|--------------------------|------------------------|-----------------------|--|------------------------|
| K- 07 10 12 71 | 5,0 | 8,0 | 40 | 10 | 3,0 |
| K- 07 10 12 73 | 5,0 | 8,0 | 40 | 10 | 6,0 |
| K- 07 10 12 75 | 5,0 | 8,0 | 40 | 10 | 7,5 |
| K- 07 10 12 80 | 6,3 | 9,5 | 60 | 10 | 3,0 |
| K- 07 10 12 82 | 6,3 | 9,5 | 60 | 10 | 6,0 |
| K- 07 10 12 84 | 6,3 | 9,5 | 60 | 10 | 7,5 |
| K- 07 10 12 78 | 6,3 | 9,5 | 60 | 10 | 10,0 |
| K- 07 10 12 89 | 8,0 | 12,0 | 80 | 9 | 3,0 |
| K- 07 10 12 91 | 8,0 | 12,0 | 80 | 9 | 6,0 |
| K- 07 10 12 93 | 8,0 | 12,0 | 80 | 9 | 7,5 |
| K- 07 10 12 87 | 8,0 | 12,0 | 80 | 9 | 10,0 |

Piederumi

K-DREHBARE VERSCHRAUBUNG Swivel adapters