

# K-ENDVERT 4-FACH WAND 20-63 INFI

4-fold terminal distributor Ø 20 mm - Ø 63 mm with wall bracket

**HANSA FLEX**

## Īpašības

Ekspluatācijas spiediens -0,99 bar - 15 bar

Temperatūras diapazons -20 °C to +80 °C

Korpuss Nickel-plated brass

Uzgrieznis Nickel-plated brass



## Izstrādājums

| Apzīmējums            | A    | Izejas pieslēgums | Ieejas pieslēgums | B    | C    | D    | E    | F1    | F2    | G    | H    | I    | L maks | L min |
|-----------------------|------|-------------------|-------------------|------|------|------|------|-------|-------|------|------|------|--------|-------|
|                       | (mm) |                   |                   | (mm) | (mm) | (mm) | (mm) |       |       | (mm) | (mm) | (mm) | (mm)   | (mm)  |
| <b>K- 07 40 54 19</b> | 87,0 | G 1/2             | G 1/2             | 73,0 | 48,5 | 120  | 77,5 | G 1/2 | G 1/2 | 5    | 28,5 | 48,0 | 60     | 35    |
| <b>K- 07 40 54 18</b> | 87,0 | G 1/2             | G 3/4             | 73,0 | 48,5 | 120  | 77,5 | G 3/4 | G 1/2 | 5    | 28,5 | 48,0 | 60     | 35    |