


Ipašības

Modelis	with pressure gauge and silencer
min. ekspluatācijas spiediens	0.20 MPa
Pneimatiskā manometra pieslēgums	Rc 1/8
Pneumatisko manometru pieslēgumu skaits	2
maks. ieejas spiediens	0,1 to 1,0 MPa
Vielas temperatūra	+2 °C to +50 °C
Vides temperatūra	+2 °C bis +50 °C
Darba vides	Saspiests gaiss



Apraksts

Booster regulator, series VBA, increases pressure only where the force is inadequate because of a low network pressure (energy saving measure), no electricity supply necessary, longer service life: doubled compared to conventional model, lower operating noise level: 13 dB (A), improved operational reliability from inbuilt mesh filter on (IN connection) compressed air inlet, reduced condensation levels: air exhaust channels integrated directly into the cylinder tube, suitable for: compressed air, size 1/4, with pressure gauge and silencer, elbow, pneumatic connection: G 1/4, pneumatic connection pressure gauge: G 1/8, pneumatic connections pressure gauge: 2, flow rate 230 l/min, pressure boost 1:2, manually actuated pressure adjustment mechanism, test pressure: 3 MPa, max. operating pressure: 2 MPa, min. operating pressure: 0.2 MPa, media temperature: +2 to +50 °C, ambient temperature: +2 to +50 °C

Izstrādājums

Apzīmējums	Pneimatiskais pieslēgums	Tipizmērs	Spiediena iestatīšanas mehānisms	Spiediena pastiprināšanas process	Caurplūde (L/min)	maks. ekspluatācijas spiediens (MPa)	Izmēģinājuma spiediens (MPa)
K- 07 60 00 07	G 1/4	1/4	manually operated	1:2 to 1:4	70	2,00	3,00
K- 07 60 00 05	G 1/4	1/4	manually operated	1:2	230	2,00	3,00
K- 07 60 00 10	G 3/8	3/8	manually operated	1:2	1000	1,00	1,50