

# K-DRUCKVERST MANO SCHALLD VBA

Booster Regulator, pressure gauge, silencer, VBA

**HANSA FLEX**

## Īpašības

|   |                                  |
|---|----------------------------------|
| Modelis                                 | with pressure gauge and silencer |
| min. ekspluatācijas spiediens           | 0.20 MPa                         |
| Pneimatiskā manometra pieslēgums        | Rc 1/8                           |
| Pneimatisko manometru pieslēgumu skaits | 2                                |
| maks. ieejas spiediens                  | 0,1 to 1,0 MPa                   |
| Vielas temperatūra                      | +2 °C to +50 °C                  |
| Vides temperatūra                       | +2 °C bis +50 °C                 |
| Darba vides                             | Saspiests gaiss                  |



## Apraksts

Booster regulator, series VBA, increases pressure only where the force is inadequate because of a low network pressure (energy saving measure), no electricity supply necessary, longer service life: doubled compared to conventional model, lower operating noise level: 13 dB (A), improved operational reliability from inbuilt mesh filter on (IN connection) compressed air inlet, reduced condensation levels: air exhaust channels integrated directly into the cylinder tube, suitable for: compressed air, size 1/4, with pressure gauge and silencer, elbow, pneumatic connection: G 1/4, pneumatic connection pressure gauge: G 1/8, pneumatic connections pressure gauge: 2, flow rate 230 l/min, pressure boost 1:2, manually actuated pressure adjustment mechanism, test pressure: 3 MPa, max. operating pressure: 2 MPa, min. operating pressure: 0.2 MPa, media temperature: +2 to +50 °C, ambient temperature: +2 to +50 °C

## Izstrādājums

| Apzīmējums     | Pneimatiskais pieslēgums | Tipizm-ērs | Spiediena iestatīšanas mehānisms | Spiediena pastiprināšanas process | Caurpl-ūde (L/min) | maks. ekspluatācijas spiediens (MPa) | Izmēģinājuma spiediens (MPa) |
|----------------|--------------------------|------------|----------------------------------|-----------------------------------|--------------------|--------------------------------------|------------------------------|
| K- 07 60 00 07 | G 1/4                    | 1/4        | manually operated                | 1:2 to 1:4                        | 70                 | 2,00                                 | 3,00                         |
| K- 07 60 00 05 | G 1/4                    | 1/4        | manually operated                | 1:2                               | 230                | 2,00                                 | 3,00                         |
| K- 07 60 00 10 | G 3/8                    | 3/8        | manually operated                | 1:2                               | 1000               | 1,00                                 | 1,50                         |