

K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

HANSA FLEX

Īpašības

| | |
|--------------------------------|--|
| maks. ekspluatācijas spiediens | 0,7 MPa |
| min. ekspluatācijas spiediens | 0.10 MPa |
| Modelis | rack and pinion |
| Vielas temperatūra | 0 °C to +60 °C |
| Vides temperatūra | 0 °C to +60 °C |
| Pagriešanas leņķis | 0 to 190° |
| Darba vides | Saspiests gaiss |
| Sērija | MSQ |
| Papildu dati | narrow pivot table unit with low overall height the rotation angle can be adjusted continuously Positioning the housing allow for quick installation the load can be mounted directly on the pivot table Air connections of 2 pages possible |



Izstrādājums

| Apzīmējums | Ø virzulis (mm) | Pneimatiskais pieslēgums | Tipizmērs | Slāpēšana | Vienības svars metrā (kg) |
|----------------|-----------------|--------------------------|-----------|---|---------------------------|
| K- 07 55 01 13 | 6 | M 3 | 1 | without, with adjustment bolt | 0,075 |
| K- 07 55 01 18 | 8 | M 5 | 2 | without, with adjustment bolt | 0,105 |
| K- 07 55 01 21 | 10 | M 5 | 3 | elastic, with adjustment bolt | 0,150 |
| K- 07 55 01 26 | 12 | M 5 | 7 | elastic, with adjustment bolt | 0,250 |
| K- 07 55 01 11 | 15 | M 5 | 10 | elastic, with adjustment bolt | 0,530 |
| K- 07 55 01 16 | 18 | M 5 | 20 | elastic, with adjustment bolt | 0,990 |
| K- 07 55 01 19 | 21 | G 1/8 | 30 | elastic, with adjustment bolt | 1,290 |
| K- 07 55 01 22 | 25 | G 1/8 | 50 | elastic, with adjustment bolt | 2,080 |
| K- 07 55 01 24 | 28 | G 1/8 | 70 | elastic, with adjustment bolt | 2,880 |
| K- 07 55 01 09 | 32 | G 1/8 | 100 | elastic, with adjustment bolt | 4,090 |
| K- 07 55 01 14 | 40 | G 1/8 | 200 | elastic, with adjustment bolt | 7,580 |
| K- 07 55 01 12 | 15 | M 5 | 10 | elastic, with integrated shock absorber | 0,540 |
| K- 07 55 01 17 | 18 | M 5 | 20 | elastic, with integrated shock absorber | 0,990 |
| K- 07 55 01 20 | 21 | G 1/8 | 30 | elastic, with integrated shock absorber | 1,290 |
| K- 07 55 01 23 | 25 | G 1/8 | 50 | elastic, with integrated shock absorber | 2,100 |
| K- 07 55 01 25 | 28 | G 1/8 | 70 | elastic, with integrated shock absorber | 2,880 |
| K- 07 55 01 10 | 32 | G 1/8 | 100 | elastic, with integrated shock absorber | 4,100 |
| K- 07 55 01 15 | 40 | G 1/8 | 200 | elastic, with integrated shock absorber | 7,650 |