

LKM HR ST DK

Spraudsavienojuma uzmava (gaiss) ar drošinātāju

HANSA FLEX

Īpašības

Modelis	Ātrā savienojuma uzmava
Savienojums 1	BSP ārējā vītne, cilindriska
Savienojums 2	
Ekspluatācijas spiediens	maks. 12 bar
Gaisa caurplūde	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Vielas temperatūra	-20 °C to +70 °C
Korpuss	Aluminium, anodised
Vītne	Nickel-plated brass
Iekšējās daļas	Stainless steel
Poga, vārsts	Hardened, galvanised steel
Bīvēšanas materiāls	NBR



Norāde

Not suitable for hitting / pulsating tools.

Citi dati pieejami pēc pieprasījuma.

Apraksts

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Izstrādājums

Apzīmējums	Savienojošās vītnes	Savienojums	Garums (mm)	SW (mm)
LKM 06 HR ST DK	G 1/4" -19	G 1/4 male	70,5	21
LKM 10 HR ST DK	G 3/8" -19	G 3/8 male	70,0	21
LKM 13 HR ST DK	G 1/2" -14	G 1/2 male	72,5	25