

# VKS ST 400

Vierkantflens, Cetop, voorlaskraag

**HANSA FLEX**

## Eigenschappen

|                             |                          |
|-----------------------------|--------------------------|
| <b>Constructie</b>          | Vierkantflens Cetop      |
| <b>Uitvoering</b>           | recht                    |
| <b>Norm</b>                 | CETOP RP 63H<br>ISO 6164 |
| <b>Materiaal</b>            | S355J2G3 (ST52.3)        |
| <b>Oppervlakbescherming</b> | Zwart geolied            |



## Artikel

| Aanduiding     | Druk PB<br>(bar) | Maat   | A<br>(mm) | Ø B<br>(mm) | C<br>(mm) | D<br>(mm) | E<br>(mm) |
|----------------|------------------|--------|-----------|-------------|-----------|-----------|-----------|
| VKS 34 ST 400  | 400              | 3/4"   | 28        | 18          | 39,5      | 32        | 45        |
| VKS 114 ST 400 | 400              | 1.1/4" | 44        | 29          | 54,0      | 44        | 55        |
| VKS 2 ST 400   | 400              | 2"     | 61        | 43          | 79,4      | 67        | 70        |
| VKS 212 ST 400 | 400              | 2.1/2" | 80        | 53          | 94,2      | 60        | 80        |
| VKS 3 ST 400   | 400              | 3"     | 90        | 58          | 104,0     | 90        | 90        |

Serie: LL = zeer licht L = licht S = zwaar - PN = nominale druk PB = max. werkdruk