

K AB

Connector, kruis-vorm

HANSA FLEX

Eigenschappen

| | |
|-----------------------|-------------------|
| Aansluiting 1 - 4 | BSP-moerdraad |
| Afdichtingsvorm 1 - 4 | 60° buitenconus |
| Constructie | Connectors |
| Uitvoering | K-vorm |
| Materiaal | Staal |
| Oppervlakbescherming | Galvanisch gecoat |



Artikel

| Aanduiding | G1 - G4 | SW (mm) | S1 - S4 (mm) |
|------------|--------------|------------|-----------------|
| K AB 02 | G 1/8" -28 | 11 | 14 |
| K AB 04 | G 1/4" -19 | 14 | 19 |
| K AB 06 | G 3/8" -19 | 19 | 22 |
| K AB 08 | G 1/2" -14 | 22 | 27 |
| K AB 10 | G 5/8" -14 | 22 | 30 |
| K AB 12 | G 3/4" -14 | 27 | 32 |
| K AB 16 | G 1" -11 | 33 | 41 |
| K AB 20 | G 1,1/4" -11 | 41 | 50 |
| K AB 24 | G 1,1/2" -11 | 48 | 60 |
| K AB 32 | G 2" -11 | 64 | 70 |

SW, S1, S2 = sleutelmaat

Productvarianten

K AB VA Connector, kruis-vorm, RVS