



### Aanwijzing

Toleranties:<br>

lengtematen volgens DIN 7715 deel 5 P2,<br>

diktematen volgens DIN 7715 deel 5 P3,<br>

### Artikel

| Aanduiding          | D<br>(mm) | d<br>(mm) | s<br>(mm) |
|---------------------|-----------|-----------|-----------|
| BOERD DI DN15 PN16  | 50,0      | 22,00     | 2,0       |
| BOERD DI DN20 PN16  | 60,0      | 28,00     | 2,0       |
| BOERD DI DN25 PN16  | 70,0      | 35,00     | 2,0       |
| BOERD DI DN32 PN16  | 82,0      | 43,00     | 2,0       |
| BOERD DI DN40 PN16  | 92,0      | 49,00     | 2,0       |
| BOERD DI DN50 PN16  | 107,0     | 61,00     | 2,0       |
| BOERD DI DN65 PN16  | 127,0     | 77,00     | 2,0       |
| BOERD DI DN100 PN16 | 162,0     | 115,00    | 2,0       |
| BOERD DI DN125 PN16 | 192,0     | 141,00    | 2,0       |
| BOERD DI DN150 PN16 | 218,0     | 169,00    | 2,0       |
| BOERD DI DN175 PN10 | 248,0     | 195,00    | 2,0       |
| BOERD DI DN200 PN16 | 273,0     | 220,00    | 2,0       |
| BOERD DI DN250 PN16 | 330,0     | 274,00    | 2,0       |
| BOERD DI DN300 PN16 | 385,0     | 325,00    | 2,0       |
| BOERD DI DN350 PN16 | 445,0     | 368,00    | 2,0       |
| BOERD DI DN400 PN16 | 497,0     | 420,00    | 2,0       |
| BOERD DI DN450 PN16 | 557,0     | 470,00    | 2,0       |