


# BOX A

BOX, A

## Eigenschappen

Constructie	O-ring
Constructie-toevoeging	Norm AS / BS
Kleur	BOX, grijs
Temperatuur min.	-30 °C
Temperatuur max.	100 °C
Temperatuur FPM min.	-15 °C
Temperatuur FPM max.	200 °C



D x d	Menge / Quantity	D x d	Menge / Quantity
2,90 x 1,78	20	12,37 x 2,62	15
3,68 x 1,78	20	13,95 x 2,62	15
4,48 x 1,78	20	15,54 x 2,62	10
5,28 x 1,78	20	17,13 x 2,62	10
6,07 x 1,78	20	18,72 x 2,62	10
7,66 x 1,78	20	20,29 x 2,62	5
9,25 x 1,78	20	21,89 x 2,62	5
10,82 x 1,78	15	23,47 x 2,62	5
12,42 x 1,78	15	18,46 x 3,53	5
14,00 x 1,78	10	20,22 x 3,53	5
15,60 x 1,78	10	21,82 x 3,53	5
17,16 x 1,78	5	23,40 x 3,53	5
18,77 x 1,78	5	24,99 x 3,53	5
9,19 x 2,62	15	26,58 x 3,53	5
10,78 x 2,62	15	28,17 x 3,53	5

## Beschrijving

BOX A bestaat uit 30 afmetingen - 340 stuks

## Artikel

Aanduiding	Materiaal	Vakken
BOX A	NBR 70 Shore A	30
BOX A FPM80	FPM 80 Shore A	30
BOX A NBR90	NBR 90 Shore A	30