



HK GEH 30 GGG

Klephuis voor inschroefbare klep SAE 3-weg GGG40

HANSA FLEX

Eigenschappen

Materiaal	GGG 40
Werkdruk	max. 350 bar
Oppervlakbescherming	Verzinkt



Artikel

Aanduiding	Ventiel- gat	A	Aansluiting 1,2	Aansluiting 3	C	D	E	F	G	G1	H	I	L	M	Gewicht
					(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)
HK GEH 38 C0830 GGG	C0830	UNF 3/4" -16	G 3/8"	G 3/8"	60	65	29	30,0	29,5	15,0	15	7	7,5	44	0,6
HK GEH 38 C1030 GGG	C1030	UNF 7/8" -14	G 3/8"	G 3/8"	70	75	39	35,5	34,5	18,5	15	7	7,5	54	1,2
HK GEH 12 C1230 GGG	C1230	UNF 1.1/16" -12	G 3/4"	G 1/2"	80	100	39	40,0	53,5	28,5	18	9	10,0	59	1,7

is toebehoren bij volgende producten

HK BFCV	3-weg stroomregeklep BFCV
HK PRRS	3-weg drukregelklep, PRRS