

# HK GEH 20 GGG

Klep huis voor inschroefbare klep SAE 2-weg GGG40

**HANSA FLEX**

## Eigenschappen

Materiaal	GGG 40
Werkdruk	max. 350 bar
Oppervlakbescherming	Verzinkt



## Artikel

Aanduiding	Ventielgat A	Aansluiting 1,2	C	D	E	F	G	H	I	L	M	Gewicht
			(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)
HK GEH 38 C0820 GGG	C0820	UNF 3/4" -16 G 3/8"	50	50	29	20	13,5	12	6	9,0	35	0,4
HK GEH 38 C1020 GGG	C1020	UNF 7/8" -14 G 3/8"	60	60	40	24	19,0	15	7	7,5	45	0,8
HK GEH 34 C1020 GGG	C1020	UNF 7/8" -14 G 3/4"	60	60	44	24	21,5	15	7	7,5	45	1,7
HK GEH 12 C1220 GGG	C1220	UNF 1.1/16" -12 G 1/2"	80	80	50	34	26,0	18	9	10,0	60	0,9
HK GEH 34 C1220 GGG	C1220	UNF 1.1/16" -12 G 3/4"	80	80	50	34	26,0	18	9	10,0	60	1,7

## is toebehoren bij volgende producten

HK EMDV	2/2-weg magneetafsluiter EMDV
HK RVPS	Drukbegegningsventiel RVPS
HK PCFC	2-weg stroomregeklep PCFC