

K-MANO U

Pressure gauges (CrNi steel type / connection radial on bottom)

HANSA FLEX

Eigenschappen

Type	232.50
Uitvoering	Bourdon-tube pressure gauge, CrNi steel type, all-stainless steel
Toepassing	For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Kwaliteitsklasse	1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm)
Mediumtemperatuur	max. +200 °C
Omgevingstemperatuur	-40 °C to +60 °C
Behuizing	CrNi steel
Kijkglas	Laminated safety glass Ø 63 = Polycarbonate



Aanwijzing

Andere gegevens op aanvraag.

Artikel

Aanduiding	Meetbereik	Ø (mm)	Aansluiting
K- 07 20 06 01	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 06 02	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 06 03	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 06 04	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 06 05	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 06 06	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 06 07	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 06 08	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 06 09	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 00 36	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 00 37	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 00 38	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 00 39	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 00 40	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 00 41	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 00 42	-1 / +15.0 bar	100,0	G 1/2"
K- 07 20 00 43	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 00 44	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 00 45	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 00 46	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 00 47	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 48	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 00 49	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 00 50	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 00 51	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 00 52	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 03 10	-1 / 0.0 bar	160,0	G 1/2"
K- 07 20 03 11	-1 / +0.6 bar	160,0	G 1/2"
K- 07 20 03 12	0 - 1.0 bar	160,0	G 1/2"
K- 07 20 03 13	0 - 10.0 bar	160,0	G 1/2"
K- 07 20 03 14	0 - 16.0 bar	160,0	G 1/2"
K- 07 20 03 15	0 - 25.0 bar	160,0	G 1/2"