

# K-PRMM ROB U

Robust diaphragm pressure gauges, connection radial on bottom

**HANSA FLEX**

## Eigenschappen

<b>Type</b>	422.12 (robust), 432.50 (chemical)
<b>Uitvoering</b>	Diaphragm pressure gauge in robust design or for chemical applications
<b>Toepassing</b>	at chemical applications in aggressive environments for gaseous or liquid media,
<b>Kwaliteitsklasse</b>	1,6
<b>Mediumtemperatuur</b>	max. +100 °C
<b>Omgevingstemperatuur</b>	-20 °C tot +60 °C
<b>Ø meetflens</b>	100 mm
<b>Behuizing, ring</b>	Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)
<b>Meetelement</b>	CrNi steel
<b>Kijkglas</b>	Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)
<b>Metermechaniek</b>	Copper alloy (robust type), CrNi steel (type for chemical applications)



## Aanwijzing

Andere gegevens op aanvraag.

## Artikel

Aanduiding	Meetbereik	Ø (mm)	Aansluiting
K- 07 20 10 99	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 00	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 11 01	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 11 02	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 11 03	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 11 04	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 11 05	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 11 06	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 11 07	0 - 25.0 bar	100,0	G 1/2"