

K-MANO ABSPH MUF ZAPF

Pressure gauge stopcocks, female - male

HANSA FLEX

Eigenschappen

Toepassing	For all pressure gauges with a flat gasket acc. to DIN 16258
Drukbereik	Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures
Temperatuur	Max. +50 °C
Behuizing	Brass with a bare metal surface or stainless steel 1.4571
Handgreep	Plastic
Testflens	-



Aanwijzing

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B
K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

Andere gegevens op aanvraag.

Beschrijving

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Extra informatie

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Artikel

Aanduiding	Schroefdraad	PN (bar)	SW (mm)	Materiaal
K- 07 20 10 94	G 1/4	6	17	Messing
K- 07 20 10 95	G 3/8	16	22	Messing
K- 07 20 10 97	G 1/2	25	27	Messing
K- 07 20 10 96	G 1/2	25	27	Stainless steel
K- 07 20 10 98	G 1/2	25	27	Messing