

# K-MANO ABSPH MUF DREH MUF

Pressure gauge stopcocks, female - loose (rotatable) female

**HANSA FLEX**

## Eigenschappen

<b>Toepassing</b>	For all pressure gauges with a flat gasket acc. to DIN 16258
<b>Drukbereik</b>	Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures
<b>Temperatuur</b>	Max. +50 °C
<b>Behuizing</b>	Brass with a bare metal surface or stainless steel 1.4571
<b>Handgreep</b>	Plastic
<b>Testflens</b>	-



## Aanwijzing

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B <br>K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B

Andere gegevens op aanvraag.

## Beschrijving

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

## Extra informatie

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

## Artikel

Aanduiding	Schroefdraad	PN (bar)	SW (mm)	Materiaal
K- 07 20 10 86	G 1/2	25	27	Messing
K- 07 20 10 87	G 1/2	25	27	Messing