

K-MANO ABSPV ZAPF SPAN MUF PRUEFFL

Pressure gauge valves, male - female/female, with test flange 60 x 25 x 10

HANSA FLEX

Eigenschappen

| | |
|--------------------------------|---------------------------------------------------------------------|
| Werkdruk | max. 250 bar brass, max. 400 bar steel/ stainless steel |
| Temperatuur | Max. +120 °C with brass/steel; Max. +200 ° C for stainless steel |
| Materiaal van alle componenten | Stainless steel |
| Afdichtmateriaal | PTFE |
| Behuizing | Brass, black-finished steel or stainless steel 1.4571 |
| Handwiel | Plastic |
| Wartelmoer spanmof | Steel |
| Ventielspil, ventielkegel | Stainless steel |



Aanwijzing

Andere gegevens op aanvraag.

Beschrijving

They are used as shut-off or reducing elements for pressure gauges when measuring liquids, gases or steam.

Artikel

| Aanduiding | Schroefdraad | PN (bar) | SW (mm) | Materiaal |
|----------------|--------------|----------|------------|-----------------|
| K- 07 20 11 34 | G 1/2 | 250 | 27 | Messing |
| K- 07 20 11 33 | G 1/2 | 400 | 27 | Stainless steel |