

K-RMM HFR STAHLBLECH CR

Standard pressure gauges with chrome-plated sheet-steel bezel, connection on rear

HANSA FLEX

Eigenschappen

Type	111.12
Uitvoering	Bourdon-tube pressure gauge, standard design, mounting ring
Toepassing	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Kwaliteitsklasse	1,6
Mediumtemperatuur	max. +60 °C
Omgevingstemperatuur	-20 °C tot +60 °C
Behuizing	Sheet steel
Materiaal meetelement en metermechaniek	Koperlegering
Kijkglas	Transparent plastic



Aanwijzing

Andere gegevens op aanvraag.

Artikel

Aanduiding	Meetbereik	Ø (mm)	Aansluiting
K- 07 20 04 37	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 38	0 - 1.0 bar	40,0	G 1/8
K- 07 20 04 39	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 40	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 41	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 42	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 43	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 44	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 45	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 46	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 41	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 42	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 43	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 44	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 45	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 46	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 47	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 48	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 49	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 50	0 - 40.0 bar	50,0	G 1/4