

K-RMM U KUNSTSTOFF MZ

Standard pressure gauges, connection radial on bottom

HANSA FLEX

Eigenschappen

Type	111.10 (radial connector on bottom)
Uitvoering	Bourdon-tube pressure gauge in standard design
Toepassing	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Kwaliteitsklasse	1.6 (Art No. K-07200303, K-07403298 - K-07201188: 2.5)
Markeerwijzer	(for Ø 160 mm - red pointer on the scale) red pointer to the window. For measuring ranges 0...0,6 bar bis 0...60 bar
Mediumtemperatuur	max. +60 °C
Omgevingstemperatuur	-20 °C tot +60 °C
Behuizing	Plastic
Materiaal meetelement en metermeechaniek	Koperlegering
Kijkglas	Transparent plastic



Aanwijzing

Andere gegevens op aanvraag.

Artikel

Aanduiding	Meetbereik	Ø (mm)	Aansluiting
K- 07 20 03 03	-1200 / 0.0 mbar	100,0	G 1/2"
K- 07 20 03 04	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 03 05	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 03 06	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 03 07	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 03 08	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 03 09	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 02 84	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 02 85	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 02 86	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 02 87	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 02 88	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 02 89	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 02 90	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 02 91	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 02 92	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 02 93	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 11 86	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 11 87	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 11 88	0 - 160.0 bar	100,0	G 1/2"